

Portable Projector

Vivitek DX28ASTAA

Value-oriented XGA short-throw projector with long-life lamp, 3D functionality and built-in audio



Features

- Bright 3,600 ANSI lumens of brightness for projection even in bright meeting rooms
- Crisp 30,000:1 contrast ratio ensuring clear presentations and sharp text
- Deliveries a large 86" image from only 1m away from the projection surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Native XGA (1024 x 768) resolution up to maximum WUXGA (1,920 x1,200)
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- 3D Ready via DLP® Link™ and HDMI v.1.4
- Audio ready with 2 watt audio speaker and audio-in/out ports
- Quiet operation with low 29dB (Eco mode) acoustic noise
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in standby mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, security bar, and power button lock

Specifications

Specifications	
Display Type	Single Chip 0.55" DLP Technology by TI
Brightness	3,600 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	WUXGA (1,920 x 1,200)
Contrast Ratio	30,000:1
Lamp Life/Type	5,000/7,000/10,000 Hours (Normal/Eco./Dynamic Eco), 210W
Throw Ratio	0.63
Image Size (Diagonal)	56" - 86"
Projection Distance	0.715m - 1.1m (2.3' - 3.6')
Projection Lens	F=2.65, f = 22.9mm
Zoom Ratio	Fixed Lens
Aspect Ratio	4:3
Offset	104%±5%
Keystone Correction	Vertical:±40°
Horizontal Frequency	15 -102kHz
Vertical Frequency	23 - 120Hz
3D Compatibility	Yes
Speaker	2W
Computer Compatibility	VGA (640 x 480) to WUXGA_RB(1920 x 1200)
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
I/O Connection Ports	HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (WxDxH)	331 x 244 x 105mm (13" x 9.6" x 4.1")
Weight	2.6kg (5.7lbs)
Available Colors	White (DX263-WH)
Noise Level	32dB/29dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	TBDW (Normal Mode), TBDW (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Carry Case, Lamp, Filter

© 2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.









Photos







