



# ET501XA

A refined presentation podium with integrated mic, auto-lift display, and multi-touch control designed to deliver seamless connectivity, effortless operation, and strong stage presence.

Features	Description
<b>1. General</b>	
Design	Slim frame design, stable structure
Material	Steel + ABS Plastic, Brushed Aluminium Finish
Dimensions (Closed)	850 × 770 × 1200 mm (L×W×H)
Dimensions (Open)	1540 × 870 × 1200 mm (L×W×H)
Sliding Cover	Easy opening/closing cover mechanism
Touch Screen	21.5" Multi-touch / Writable Display
Display Specs	1920×1080 resolution; 250 cd/m <sup>2</sup> brightness; 1000:1 contrast
Viewing Angle	170° (H), 170° (V)
Touch Durability	30 million touch cycles
Response Time	5 ms
Microphone	Gooseneck MIC with ON/OFF control
Output Ports	Max 3 KW
Laptop Interface Modules	Power ×1, USB ×2, Audio ×1, VGA ×1, Sound In ×1, HDMI ×1, RJ45 ×1
Power Distributor	110V–240V AC, 50Hz/60Hz
Mobility	4 soft caster wheels for easy movement
Maintenance	Simple repair, service, and management
Other Features	Fast position sensing & quick response



Specifications are subject to change without notice.